TMP light

Confronto modelli S2216K

	S2216SKS220A	S2216SKS220B	S2216SKS220C	S2216SKS220F	S2216SKS220G	S2216SKS220N	S2216SKS220R	S2216SKS220S	S2216SKS220T	S2216SKS220V
Lumen/m	783lm		873lm	996lm	873lm	945lm		945lm	819lm	
Gradi Kelvin	1800K	Colorate	3000K	6000K	2700K	4000K	Colorate	6000K	2100K	Colorate
Colore Luce	Warm White, 1800K	Blue light	Warm White, 3000K	Cold White, 6000K	Warm White, 2700K	Natural White, 4000K	Red light	Cold White, 6000K	Warm White, 2100K	Green light
Certificazioni	CE,RoHS,TUV,UL	CE,RoHS,TUV,UL	CE,RoHS,TUV,UL	CE,RoHS,TUV,UL	CE,RoHS,TUV,UL	CE,RoHS,TUV,UL	CE,RoHS,TUV,UL	CE,RoHS,TUV,UL	CE,RoHS,TUV,UL	CE,RoHS,TUV,UL
x			0.4374							
y			0.3992							
CRI	Ra>90		Ra>90	Ra>90	Ra>90	Ra>90		Ra>90	Ra>90	
Alimentazione	24,0Vdc	24,0Vdc	24,0Vdc	24,0Vdc	24,0Vdc	24,0Vdc	24,0Vdc	24,0Vdc	24,0Vdc	24,0Vdc
Gradi lente	120°	120°	120°	120°	120°	120°	120°	120°	120°	120°
Potenza massima	9,0W	9,0W	9,0W	9,0W	9,0W	9,0W	9,0W	9,0W	9,0W	9,0W
Nr. Led/m	182	182	182	182	182	182	182	182	182	182
Dimmerabile	SI	SI	SI	SI	SI	SI	SI	SI	SI	SI
Sezionabile	38,5mm	38,5mm	38,5mm	38,5mm	38,5mm	38,5mm	38,5mm	38,5mm	38,5mm	38,5mm
Lumen/Watt	87		97	111	97	105		105	91	
Dimensione mm	5000mm	5000mm	5000mm	5000mm	5000mm	5000mm	5000mm	5000mm	5000mm	5000mm
Modello led	2216	2216	2216	2216	2216	2216	2216	2216	2216	2216
Attacco	Cavo	Cavo	Cavo	Cavo	Cavo	Cavo	Cavo	Cavo	Cavo	Cavo
MacAdam	SDCM<3		SDCM<3	SDCM<3	SDCM<3	SDCM<3		SDCM<3	SDCM<3	
Confezione	Bag	Bag	Bag	Bag	Bag	Bag	Bag	Bag	Bag	Bag
Classe energetica	G		F	F	F	F		F	G	
Grado IP	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20	IP20
Grado IK	IK02	IK02	IK02	IK02	IK02	IK02	IK02	IK02	IK02	IK02